



SPECIFICATIONS

- Current Rating: 1.5 Amps
- Voltage Rating: 150V AC
- Contact Material: 0.35mm Thick Phosphor Bronze
- Contact Plating: Gold plated
- Contact Resistance: 20mΩ Max.
- Housing Material: Nylon 46 thermoplastic UL94V-0
- Insulation Resistance: 500MΩ Min.

Available With LEDs

Series	Contacts	Positions	Type	Color	Plating	Options	Panel Grounds
CTJ	6	06	714	BK	PX	S	PG3
Ganged Modular Jack	6=6 Contacts	06=6 Positions	Type=714	BK=Black	P1=15u" Gold P2=30u" Gold P3=50u" Gold	[blank]=No Shield S=Full Shield	[blank]=None 1=Top 3=Top & Sides

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	06/14/07
				Checked	Lizzy	06/14/07
				Drawn	Tina	06/14/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-6-06-714-BK-PX**

Description: Modular Jack Side Entry W/O LEDs

