



**SPECIFICATIONS**

Housing: DSM Stanyl TE250F6 (Nylon-46)  
 Heat Deflection Temp 290°  
 Black Color, UL94V-0  
 Contacts: 0.35mm Thick Phos-Bronze  
 Plated With Hard Gold & Gold Flash In Solder Area

Series	Positions	Contacts	Body Style	Color	Plating	Options
CTJ	X	XX	A	BK	XX	XX
Modular jack	6=6 positions 8=8 positions 10=10 positions	06=6 contacts 08=8 contacts 10=10 contacts	A body style	BK=Black	P1=15µ" gold P2=30µ" gold P3=50µ" gold	[blank]=None WF=Without Flange MS=Shielded face SM=Surface mount

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/19/07
				Checked	Lizzy	07/19/07
				Drawn	Tina	07/19/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: in		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-6-06-A-BK-XX-SM**

Description: Side Entry SMT Version PCB Jack