



SPECIFICATIONS

Voltage Rating: 125 VAC RMS
 Current Rating: 1.5 Amps@25°C
 Housing Material: PBT UI94V-0
 Contact Material: Phosphor Bronze, T=0.35mm
 Contact Plating: Selective Gold Plating
 Tin over Nickel on Tails
 Mating/Unmating Force: 30N Max
 Retention Strength: 50N for 60s
 Durability: 750 Cycles Min
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 1000 MΩ Min @500VDC
 Withstanding: 1000 VAC RMS, contact to contact
 1500VDC, contact to screen

Series	Positions	Contacts	Style	Color	Plating	Options
CTJ	X	XX	D4	BK	PX	XX
Modular Phone Jack	4-10	02-10	D4 style	BK=Black	X: 0=6u" 1=15u" 2=30u" 3=50u"	Blank=None WF=No Flange FS=Full Shield SM=Surface Mount

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/29/09
				Checked	Lizzy	05/29/09
				Drawn	Tina	05/29/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		


Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-6-XX-D4-BK-PX-XX**

Description: Modular Phone Jack, Top Entry, Split Peg