



**SPECIFICATIONS**

Housing: ABS HB, Black  
 Contact: Phosphor Bronze, Gold Plating 6u"  
 Wire: UL-1061 E41396 AWM80 C VW-1 300V 26AWG  
 Insulation Resistance: 10MΩ or more  
 Withstanding: AC 500V 1 Minute  
 Contact Resistance: 20mΩ Minimum  
 Current Rating: 1.5mA

Jack	Color
1	NC
2	NC
3	Blue
4	Yellow
5	Green
6	Red
7	Black
8	White
9	NC
10	NC

Series	Posi-tions	Contacts	Body Style	Color	Plating	Wired Length
CTJ	8	08	641A	XX	P0	XXX
Modular jack, single position	8	8	Wired Mod Jack See drawing	BK=Black GY=Gray	P0=6μ" GD (std)	006=6"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/30/10
				Checked	Lizzy	08/30/10
				Drawn	Tina	08/30/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-8-08-641A-XX-P0-XXX**

Description: Wired modular phone jack

