



PCB LAYOUT

SPECIFICATIONS

Contact: 0.35mm Phosphor Bronze
 Plating: Gold Plated
 Gold flash in solder area
 Housing: Nylon 46 thermoplastic UL94V-0
 Or Nylon ZYTEL FR-52
 Color: Black
 Hold Down: 0.35mm Copper Alloy
 Plating: Tin

| Series | Positions | Contacts | Style | Color | Plating |
|-------------------------------|-------------|------------|-----------|----------|--|
| CTJ | 8 | 08 | 700 | BK | PX |
| Modular jack, single position | 8 positions | 8 contacts | 700 style | BK=Black | P1=15μ" gold P2=30μ" gold P3=50μ" gold |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|------------|-------------|-------------|
| | | | | Approved | Howard | 09/22/11 |
| | | | | Checked | Lizzy | 09/22/11 |
| | | | | Drawn | Tina | 09/22/11 |
| | | | | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles ± 3' |
| | | | | UNIT: mm | | |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-8-08-700-BK-PX**

Description: 8 Pos. Solder Tab-Inside Side Entry SMT Type