



PC Board Layout

**SPECIFICATIONS**

Current Rating: 1.5 Amps  
 Contact Resistance: 20mΩ Max.  
 Withstanding: 1000V rms. 60Hz  
 Insulation Resistance: 600MΩ Min.  
 Housing: PBT Thermoplastic UL94V-0, Black  
 Contact: 0.45mm Dia. Phosphor Bronze  
 Plating: Gold Plated 6u", 15u", 30u", 50u" (optional)  
 Shield: Copper Alloy 0.25mm thick, Nickel Plating

Series	Positions	Contacts	Body Style	Plating	Options
CTJ	X	XX	951	PX	XX
Modular jack, single position	4-8	02-08	Side Entry Tab Down	P0=6μ" P1=15μ" P2=30μ" P3=50μ"	Blank=None FS=Full shield

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/03/03
				Checked	Lizzy	12/03/03
				Drawn	Tina	12/03/03
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-8-08-951-BK-PX-FS**

Description: Modular phone jack, side entry bottom tab