



SPECIFICATIONS

Housing material: PBT polyester, mixed glass fiber, UL94V-0, black
 Contact material: Phosphor bronze, ø0.45mm
 Contact plating: Gold
 Shield material: Copper alloy 0.25mm
 Shield plating: Nickel

NOTE: Cavity conforms to FCC rules and regulations Part 68, subpart F

RoHS compliant

Series	Positions	Contacts	Style	Color	Plating	Options
CTJ	X	XX	C	BK	PX	XX
Modular jack, single position	4=4 positions 6=6 positions 8=8 positions	02=2 contacts 04=4 contacts 06=6 contacts 08=8 contacts	C Style	BK=Black	P1=15µ" gold P2=30µ" gold P3=50µ" gold	[blank]=None FS=Fully shielded

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-8-08-C-BK-PX-FS**

Description: Modular jack, PCB mount, side entry, mini low profile, 8 positions, shielded