



SPECIFICATIONS

Contact material: Phosphor bronze alloy 0.35 mm

Contact plating: Hard gold on contact area

Tin on tail area

Housing material: PBT with 15% glass fiber, UL94V-0

Shield material: Copper alloy 0.25mm

Shield plating: Nickel

Series	Positions	Contacts	Style	Color	Plating	Options
CTJ	X	XX	D	BK	PX	XX
Modular jack	4,6,8,10	02,04,06,08,10	D style	BK=Black	P1=15µ" gold P2=30µ" gold P3=50µ" gold	[blank]=Flange WF=No flange KY=Keyed FS=Full shield

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
A	PNT	6/30/09	Greg	Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-8-08-D-BK-PX-FS**

Description: Modular jack, top entry, shielded

