



**SPECIFICATIONS**

Housing material: PBT with mixed glass fiber, UL94V-0  
 Contact material: Phosphor bronze 0.35mm  
 Contact plating: Gold on mating area, tin on solder area  
 Shield material: Copper alloy 0.25mm  
 Shield plating: Tin  
 Note: Cavity conforms to FCC rules and regulations Part 68, Subpart F

Series	Positions	Contacts	Style	Color	Plating	Options
CTJ	X	XX	D2	BK	PX	XX
Modular jack, single position	8=8 positions 10=10 positions	06=6 contacts 08=8 contacts 10=10 contacts	D2=Style D2	BK=Black	P1=15μ" P2=30μ" P3=50μ"	[blank]=None FS=Full shield

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/10/01
				Checked	Lizzy	03/10/01
				Drawn	Tina	03/10/01
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-8-08-D2-BK-P1-FS**

Description: Modular jack, 8 position, flat pin, shielded, top entry, PCB mount