



SPECIFICATIONS

- Voltage Rating: 125 VAC RMS
- Current Rating: 1.5 Amps@25°C
- Housing Material: PBT UI94V-0
- Contact Material: Phosphor Bronze, T=0.35mm
- Contact Plating: Selective Gold Plating
- Mating/Unmating Force: 30N Max
- Retention Strength: 50N for 60s
- Durability: 750 Cycles Min
- Contact Resistance: 20m Ω Max.
- Insulation Resistance: 1000 M Ω Min @500VDC
- Withstanding: 1000 VAC RMS
- Tin over Nickel on Tails

| Series | Positions | Contacts | Style | Color | Plating | Options |
|--------------------|-----------|----------|----------|----------|---|--|
| CTJ | X | XX | D4 | BK | PX | XX |
| Modular Phone Jack | 4-10 | 02-10 | D4 style | BK=Black | X: 0=6u" 1=15u" 2=30u" 3=50u" | Blank=None WF=No Flange FS=Full Shield SM=Surface Mount |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|----------------|-----------------|----------------------|
| | | | | Approved | Howard | 05/29/09 |
| | | | | Checked | Lizzy | 05/29/09 |
| | | | | Drawn | Tina | 05/29/09 |
| | | | | 0.0 \pm 0.35 | 0.00 \pm 0.20 | Angles $\pm 3^\circ$ |
| | | | | UNIT: mm | | |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-8-08-D4-BK-PX-XX**

Description: Modular Phone Jack, Top Entry, Split Peg