



UNIT:mm

SPECIFICATIONS

- Turn Ratio: Transmit=1CT:1CT
Receive=1CT:1CT
- Insertion Loss: -1.0dB MAX.
- Return Loss: -18dB(1-30MHz), -16dB(40MHz)
-12dB(50MHz), -10dB(60-80MHz)
- Cross Talk: -40dB(30MHz), -35dB(60MHz), -30dB(100MHz)
- Common Mode Rejection: -30dB(30MHz), -20dB(60MHz), -20dB(100MHz)
- HI-Pot Test: 1500Vrms/0.5mA
- OCL: 350uH MIN @100KHZ/0.1V/8mA DC Bias
- Operating Temperature: 0°C ~ +70°C

Series	Positions	Contacts	Body Style	Color	Plating	Options	Panel Grounds
CTJ	8	08	F1364G	BK	PX	XX	PGX
Modular Jack	8 Positions	8 Contacts	F1364G Style	BK=Black	P1=15u" gold P2=30u" gold P3=50u" gold	[blank]=None FS=Full Shield	2=Top 4=Sides 6=Top & Sides

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	09/15/08
				Checked	Lizzy	09/15/08
				Drawn	Tina	09/15/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-8-08-F1364G-BK-P1-FS-PG6**

Description: Magnetic Through Hold Tap-UP RJ-45 Jack