



SPECIFICATIONS
Housing material: Nylon 46, UL94V-0, black
Contact material: Phosphor bronze 0.35mm
Contact plating: Hard gold, gold flash in solder area
Shield material: Copper alloy 0.25mm
Shield plating: Nickel
Note: Conforms to FCC rules and regulations, Part 68, subpart F

RoHS compliant

Series	Mold Size	No. of Contacts	Mold Style	Mold Color	Plating	Options	Special Options
CTJ	8	XX	A	BK	P1	MS	SM
Modular phone jack	Size 8	08=8 contacts 10=10 contacts	A style	BK=Black GY=Gray	P1=15μ" gold P2=30μ" gold P3=50μ" gold	MS=Metal face shield	SM=Surface mount

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-8-10-A-BK-P1-MS-SM**

Description: PCB jack, side entry, low profile, SMT type, shielded

