



PCB LAYOUT / TOP VIEW

position	contact	A	B	C	D
<8P>6P	4C/6C	18.00	15.50	10.00	11.43
8P	4C/6C/8C	18.00	15.50	11.90	11.43
10P	10C	18.00	15.50	11.90	11.43

SPECIFICATIONS

- Voltage Rating: 125V
- Current Rating: 1.5A
- Contact Material: Phosphor Bronze
- Contact Plating: Gold over nickel in contact
Tin Plating on solder area
- Contact Resistance: 30 milliohms max.
- Housing Material: PBT, UL94V-0, Black/Grey
- Insulation Resistance: 500 megaohms min.
- Durability: 750 cycles min.
- Withstanding: 1000V
- Temperature Range: -40C to +80C

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/07/09
				Checked	Lizzy	12/07/09
				Drawn	Tina	12/07/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-8-XX-D-BK-PX**

Description: Modular Jack 260 8P Top Entry

