



SPECIFICATIONS

Housing material: PBT polyester with glass fiber, UL94V-0

Contact material: Phosphor bronze, $\phi 0.35\text{mm}$

Contact plating: Gold on contact area

Tin on solder area

Cavity conforms to FCC regulation Part 68, Subpart F

RoHS compliant

Series	Positions	Contacts	Body Style	Color	Plating	Options
CTJ	8	XX	D2HP	XX	PX	XX
Modular phone jack	6=6 positions 8=8 positions 10=10 positions	06=6 contacts 08=8 contacts 10=10 contacts	Style D2 HP=Half peg	BK=Black GY=Gray	P1=15 μ " gold P2=30 μ " gold P3=50 μ " gold	[blank]=None FS=Full shield KY=Keyed WF=Without Flange

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	11/10/02
				Checked	Lizzy	11/10/02
				Drawn	Tina	11/10/02
				0.0 \pm 0.35	0.00 \pm 0.20	Angles \pm 3°
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-8-XX-D2HP-XX-PX-WF**

Description: Modular phone jack, 8 position, flat peg, top entry, PCB mount