


SPECIFICATIONS

- Rated Voltage: 300V
- Rated Current: 10A
- Contact Resistance: 20mΩ
- Insulation Resistance: 5000MΩ / 1000V
- Withstanding: AC1500V / 1Min
- Screws: M3 Steel Zinc Plated
- Wire Guard: Phosphor Bronze Ni Plated
Or Stainless Steel
- Pin Header: Brass, Tin Plated
- Housing: PBT, UL94V-0
- Max Soldering: +250C for 5 Sec.
- Torque: 0.5Nm (4.5LB.In)
- Strip Length: 5.4-5mm
- Temp Range: -30C ~ +120C



Series	Type	Pitch	Positions	Plating	Color
CMTB	F300MVP	XXX	XX	XX	XX
Terminal block	See drawing	500=5.00mm 750=7.50mm (705)	02, 03, 08, 16	TN=Tin GD=Gold Flash GD30=30μ GD	GN=Green BK=Black BL=Blue RD=Red

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/15/12
				Checked	Lizzy	08/15/12
				Drawn	Tina	08/15/12
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CMTB-F300M-500-XX-XX**

Description: Terminal block. Top screw, side entry, modular