


SPECIFICATIONS

Current Rating: 1 Amp
 Contact Material: Brass
 Contact Resistance: 20mΩ Max.
 Insulation Material: Polyester, UL94V-0
 Insulation Resistance: 1000MΩ Min.
 Withstanding: 300V AC
 Operating Temp: -40C to +105C

RECOMMENDED P.C.B LAYOUT



Series	Height H (mm)	No. of Rows	Type	No. of Pins	Mating Length A	Plating	Options
CPH	X	X	XX	XX	XX	XX	XX
Pin header, DIP type, .40mm square pins	[blank]=1.50, B=1.00, C=1.70*, D=2.00, E=2.54* F=2.70* G=3.00* *Dual row only	2=Dual rows 1=Single row	[blank]=Straight SM=Surface mount RA=Right angle	2-33 (single row) 4-66 (double row)	SA=1.9mm mating length SB=3.00mm mating length SC=3.50mm mating length CS=Cust. Specified length	TN=Tin SGXX=Selective Gold GDXX=Gold XX=flash if blank, 5, 10, 15, 30u"	[blank]=None CP=Centering pin HT=Hi Temp PPL=Pick cap TR=Tape & reel TB=Tube

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CPH-X-2-SM-XX-XX-XX-XX**

Description: 1.27 Pin Header Dual Rows SMT Type

