



SPECIFICATIONS

Impedance: 50Ω
 Frequency Range: 0-6GHz
 Withstanding Voltage: 500V rms
 VSWR Straight: ≤ 1.15
 VSWR Right Angle: ≤ 1.25
 Center Contact Res.: ≤ 5mΩ
 Outer Contact Res.: ≤ 2.5mΩ
 Insulation Resistance: ≥ 1000MΩ
 Durability: >500
 Temperature Range: -65C ~ +165C

Name	Material	Finish
Body	Brass	Gold Plated
Center Conductor	Brass	Gold Plated
Crimping Suite	Copper Alloy	Nickel or Gold Plating
O-Ring Seal	6146 Silastic	
Insulator	PTFE	

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	06/01/07
				Checked	Lizzy	06/01/07
				Drawn	Tina	06/01/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CRF-MMCX-8524-BGTG-A**

Description: MMCX R/A CRIMP PLUG, RG174/U, 188A/U, 316/U CABLE