



PC Board Layout

**SPECIFICATIONS**

Insulation Resistance: 1000 Megohms min.  
 Withstanding Voltage: 1000V AC/minute  
 Durability: 600 mating cycles min.

Tolerances Unless Otherwise Specified:  
 0-10:±0.1;10-20:±0.15;  
 20-30:±0.2

Series	Positions	Contacts	Type	Color	Plating	Options
CTJ	10	10	AS	BK	PX	XX
Modular jack, single port	10 pos	10 contacts	Type AS	BK=Black	P0=6µ" gold P1=15µ" gold P2=30u" gold P3=50u" gold	[blank]=None MS1=Face shield KY=Keyed WF=No Flange

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	04/02/07
				Checked	Lizzy	04/02/07
				Drawn	Tina	04/02/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-10-10-AS-BK-P1-MS1**

Description: 10P Modular Jack w/ Face Shield