



SPECIFICATIONS
 Insertion loss: -1/1-65 MHz
 Return loss: -20/1-10 MHz; -16/30MHz; -12/60-80MHz
 Crosstalk: -40/1-10MHz; -35/32-60MHz; -30/50-100MHz
 Com. Mode reject.: -30/1-50MHz; -20/50-130MHz

Series	Positions	Contacts	Style	Color	Plating	Options	Panel Grounds
CTJ-A2	10	10	44FLPY	BK	PX	XX	XX
Mod jack with 2 USB type A	10=10 positions	10=10 contacts	Style 44 F with green/orange and yellow LEDs	BK=Black	P1=15μ" gold P2=30μ" gold P3=50μ" gold	FS=Full shield	[blank]=None PG2=Top PG4=Sides PG6=Top & sides

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/03
				Checked	Lizzy	08/10/03
				Drawn	Tina	08/10/03
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-A2-10-10-44FLPY-BK-P1-FS-PG6**

Description: Modular jack, magnetic filtered, RJ45

