



**SPECIFICATIONS**  
 Insertion loss: -1/1-100 MHz  
 Return loss: -18/1-30MHz  
 -16/30-60MHz  
 -12/60-80MHz  
 Crosstalk: -30/1-100MHz  
 Com. Mode reject.: -30/1-100MHz

Series	Positions	Contacts	Style	Color	Plating	Options
CTJ-A2	8	08	45FLOW	BK	PX	XX
Mod jack with 2 USB type A	8=8 positions	08=8 contacts	Style 45F with orange/orange and green LEDs	BK=Black	P1=15µ" gold P2=30µ" gold P3=50µ" gold	FS=Full shield

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/12/04
				Checked	Lizzy	07/12/04
				Drawn	Tina	07/12/04
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-A2-8-08-45FLOW-BK-P1-FS**

Description: Modular jack, magnetic filtered, RJ45