



SPECIFICATIONS

Contact material: Phosphor bronze 0.35mm
 Contact plating: Gold over nickel on contact area
 Tin over nickel on solder tails
 Housing material: PBT with glass fiber, UL94V-0
 Shield material: Brass 0.20mm
 Shield plating: Nickel

PC Board Layout (Top View)

Dimensions						
Position	Contact	A	B	C	D	E
6	2/4/6	15.60	13.65	13.40	10.16	9.90
8	8	17.50	15.65	15.40	11.43	11.85
10	10	17.50	15.65	15.40	11.43	11.85

Series	Positions	Contacts	Style	Color	Plating	Options
CTJ	X	XX	285S	BK	PX	XX
Modular jack	6, 8, 10	2, 4, 6, 8, 10	Side entry PCB mount tab down	BK=Black	P1=15μ" gold P2=30μ" gold P3=50μ" gold	[omitted]=None MS=Metal face

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	11/06/03
				Checked	Lizzy	11/06/03
				Drawn	Tina	11/06/03
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-X-XX-285S-BK-PX-MS**

Description: Modular phone jack, side entry PCB mount, tab down