



**SPECIFICATIONS**

Housing: Nylon 46 UL94V-0, Black  
 Contacts: 0.45mm Diameter Phos-Bronze Gold Plating

No. of Positions	No. of Contacts	A	B	C
4	4	11.20	7.62	7.85
6	2/4/6	13.20	10.16	9.90
8	6/8	15.20	11.43	11.95

Series	Positions	Contacts	Type	Color	Plating	Options
CTJ	X	XX	951N	BK	PX	X
Modular Jack	4=4 Positions 6=6 Positions 8=8 Positions	02=2 Contacts 04=4 Contacts 06=6 Contacts 08=8 Contacts (see table)	Type=951N	BK=Black	P1=15u" Gold P2=30u" Gold P3=50u" Gold	Blank=None KY=Keyed (8 pos only)

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	10/15/07
				Checked	Lizzy	10/15/07
				Drawn	Tina	10/15/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-8-08-951N-BK-PX-X**

Description: Low Profile PCB Phone Jack Type 951N CAT5E