



Dimensions						
Positions	Contacts	A	B	C	D	E
6	2, 4, 6	15.75	14.00	9.90	10.16	13.75
8	4, 6, 8	17.70	16.00	11.93	11.43	15.75
10	10	17.70	16.00	11.93	11.49	15.75

**SPECIFICATIONS**

Contact material: Phosphor bronze 0.35mm  
 Contact plating: Gold on contact area  
 Gold flash on solder tail area  
 Housing material: PBT + 15% glass fiber, UL94V-0  
 Shield material: Brass 0.25mm  
 Shield plating: Nickel

Series	Positions	Contacts	Body Style	Color	Plating	Options
CTJ	X	XX	A	BK	PX	XX
Modular jack, single port	6,8,10	02,04,06,08,10	A style	BK=Black	P1=15 $\mu$ " gold P2=30 $\mu$ " gold P3=50 $\mu$ " gold	[blank]=None MS=Face shield KY=Keyed WF=No Flange

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
A	PNT	06/30/09	Greg	Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 $\pm$ 0.35	0.00 $\pm$ 0.20	Angles $\pm$ 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-X-XX-A-BK-PX-MS**

Description: Modular jack, shielded face, PCB mount