



PCB LAYOUT/TOP VIEW

SPECIFICATIONS

Voltage rating:	120VAC
Current rating:	1.5 amps
Contact material:	Phosphor bronze, Ø0.45mm
Contact plating:	Hard gold
Contact resistance:	20 milliohms max.
Housing:	PBT Polyester, UL94V-0, black
Insulation resistance:	500 megohms min.
Shield material:	Copper alloy 0.20mm
Shield plating:	Tin over nickel
Withstanding:	1,000VAC for 1 min.

Series	Positions	Contacts	Style	Color	Plating	Options
CTJ	X	XX	C7	BK	PX	FS
Modular jack	6, 8, 10	4-10	C7 style	BK=Black	1=15u" gold 2=30u" gold 3=50u" gold	FS=5 side shield

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTJ-X-XX-C7-BK-PX-FS**

Description: Modular jack, side entry, 5 side shield