



SPECIFICATIONS

Insulation Resistance: 1000 Megohms Min.
 Withstanding: 1000V, AC/minute
 Durability: 1000 Mating Cycles min
 Wire Gauge: 26 AWG Max.

| Item | Name | Description |
|------|----------------|-------------------|
| 1 | 10P10CS Plug | |
| 2 | Blade | QSn6.5-0.1 T=0.35 |
| 3 | 10P10CS Shield | H65Y T=0.2 |

| Series | Plug Size | Contacts | Plating | Options |
|--------------|-------------|----------------|--|-----------------|
| CTP | XX | X | PX | MS |
| Modular plug | 4, 6, 8, 10 | 2, 4, 6, 8, 10 | P1=15µ" gold P2=30µ" gold P3=50µ" gold | MS=Metal shield |

RoHS compliant

| Rev. | Description | Date | Approved | Drawing | Name | Date |
|------|-------------|------|----------|------------|-------------|-------------|
| | | | | Approved | Howard | 03/20/09 |
| | | | | Checked | Lizzy | 03/20/09 |
| | | | | Drawn | Tina | 03/20/09 |
| | | | | 0.0 ± 0.35 | 0.00 ± 0.20 | Angles ± 3' |
| | | | | | UNIT: mm | |

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CTP-10-10-PX-MS**

Description: 10P10C Modular Plug, Shielded