


SPECIFICATIONS

- Current Rating: 1.5 Amps
- Insulation Resistance: 1000 Megohms Min.
- Contact Resistance: 30 Milliohms Max
- Mating Force: 2.5Kg Max
- Unmating Force: 1Kg Min
- Contacts: Copper Alloy
- Shell: Copper Alloy
- Withstanding: AC 500V
- Operating Temp: -55C to +85C

Recommend PCB LAYOUT



RoHS compliant

Series	Type	Version	Gender	Shield Finish	Insulator Color	Contact
CUSB	B	204B	F	X	XX	XX
USB Connector	Type B	Vertical, Shielded	F=Female	N=Nickel T=Tin	BK=Black WT=White	GD=Gold Flash (ver. 2.0) GD30=30u" Gold (ver 2.01)

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/21/08
				Checked	Lizzy	08/21/08
				Drawn	Tina	08/21/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-204B-F-X-XX-XX**

Description: USB-B Female 180 DIP