



**SPECIFICATIONS**

Current Rating: 1.5A/contact terminal  
 Voltage Rating: 30V DC  
 Contact Resistance: 30 milliohms Max.  
 Insulation Resistance: 1000Mohms Min.  
 Mating Force: 3.75kgf max  
 Unmating Force: 1.02kgf min  
 Housing: Thermoplastic, LCP Black  
 Contact: Copper Alloy C2680  
 Shell: Copper Alloy C2680/SPCC  
 Contact Plating: Gold in Mating, Tin on Solder  
 Shell Plating: Nickel Plating  
 Package: Tray  
 Withstanding: 500V AC

Series	Type	Style	Type	Insulator	Contact Plating	Color
CUSB	A	04F	XX	X	SGXX	X
USB Connector	Type A	4 Contact Female	RA=Side Entry RASM=RA Surface Mount	B=PBT L=LCP	SG=Selective Gold XX=Flash if blank 3,6,15,30,50u in	K=Black (std) W=White

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/15/09
				Checked	Lizzy	05/15/09
				Drawn	Tina	05/15/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-A-04F-RASM-X-SGXX-X**

Description: USB Upright Right Angle SMT A Type Female