


**SPECIFICATIONS**

Current Rating: 1 Amp Max  
 Contact Resistance: 30m OHMS Max  
 Insulation Resistance: 1000M OHMS Min at DC 500V  
 Housing: Hi-Temp Plastic, UL94V-0  
 Shell: Stainless Steel, Nickel Plating  
 Terminal: Copper Alloy, Gold plating on contact area  
 Tin Plating on solder tail

Withstanding: 500V AC for 1 minute  
 Operating Temp: -55°C ~ +105°C



P.C.B. LAYOUT

Series	Type	Style	Gender/Cont/Mount	Shell Plating	Contact Plating	Color	Options
CUSB	A	202DH	F4S	N	SGXX	WT	KT
USB Connector	A=Type A	Side entry for board cutout	F4S=Female 4 Contacts, Surface mount	N=Nickel	SG=Selective Gold XX=Flash if blank, 5, 10, 15, 30u"	WT=White	KT=Kinked Tail

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/22/10
				Checked	Lizzy	03/22/10
				Drawn	Tina	03/22/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-A-202DH-F4S-N-SGXX-WT-KT**

Description: USB A Female Surface Mount, for Board Cutout