



SPECIFICATIONS

Current Rating: 1.5 Amp Max
 Withstanding: 500V AC for one minute
 Contact Resistance: 30m Ohms Max
 Insulation Resistance: 1000M Ohms Max
 Housing: Hi-Temp Plastic (UL94V-0)
 Shell: SPCC, Nickel Plating
 Terminal: Copper Alloy, Gold Plating on Contact Area
 Tin Plating on Solder Tail
 Operating Temp: -25C ~ +105C

Series	Type	Style	Contacts	Shell Plating	Contact Plating	Color	Option
CUSB	A	22ADHX	4	X	SGXX	XX	CP
USB Connector	Type A	Edge Mount, Side Entry, SMT, Shielded X: M=Male F=Female	4 Contacts	N=Nickel T=Tin	SG=Selective Gold XX=Flash if blank (v1.1) 5,10,15,30u" Gold (V2.0)	WT=White BK=Black BG=Beige	CP=Centering Pegs

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/24/12
				Checked	Lizzy	07/24/12
				Drawn	Tina	07/24/12
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-A-22ADHM-4-SGXX-XX-CP**
 Description: USB A Type, SMT Board Cut Type H:2.00, Metal Shield, With Post, Male