



PCB LAYOUT

**SPECIFICATIONS**

Voltage Rating:	30V AC/DC
Rated Current:	1.5A AC/DC
Withstanding:	500V / minute
Housing:	PBT UL94V-0 White
Contact:	Brass
Shell:	SPCC
Insulation Resistance:	1000 Megohms Min
Contact Resistance:	30 Milliohms Max.
Operating Temp:	-25°C to +80°C

Series	Type	Style	Version	Housing	Shell	Shell Plating	Contacts	Contact Plating	Color	Package
CUSB	A	ASP6	1F4RT	P	S	N	B	GD	WT	XX
USB Connector	Type A	See Drawing	Single Port Female 4 Contacts, Side Entry Through Hole	P=PBT	S=Steel	N=Nickel (std)	B=Brass	GD=Gold	WT=White	TY=Tray TR=Tape & Reel TB=Tube

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	04/17/12
				Checked	Lizzy	04/17/12
				Drawn	Tina	04/17/12
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-A-ASP6-1F4RT-PSNB-GD-WT-XX**

Description: USB type A female shielded through hole plus SMT mounting