


PCB EDGE  
 RECOMMENDED PCB LAYOUT  
 TOLERANCE: ±0.05



**SPECIFICATIONS**

- Current Rating: 1.5 Amperes
- Withstanding: AC 500V at Sea Level
- Insulation Resistance: 1000 Megohms Min
- Contact Resistance: 30 Milliohms Max.
- Mating Force: 3.5 kgf. Maximum
- Unmating Force: 1 kgf Minimum
- Contact: Copper Alloy, Gold Plated
- Insulator: LCP, UL94V-0
- Shell: Copper Alloy, Nickel Plated
- Operating Temp: -55°C ~ +85°C

Series	Type	Style	Version	Material	Shell Plating	Contact Plating	Color	Option	Package
CUSB	A	CS205	1F4RST	X	X	SGXX	XX	XX	XX
USB Connector	Type A	See Drawing	Single Port Female 4 Contacts, Side Entry Through SMT + Thru Hole	L=LCP	N=Nickel (std) G=Gold T=Tin	SGXX=Selective Gold XX=Flash (v1.1) if blank, 30=30u" (v2.0)	BK=Black BG=Beige	KT=Kinked Tail	TR=Tape & Reel

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date	<b>Central Components Manufacturing</b> 440 Lincoln Blvd., Middlesex, New Jersey 08846 Phone 732 469-5720 888 288-5152 Fax 732 469-1919		
				Approved	Howard	07/31/15	<b>Part No.: CUSB-A-CS205-1F4RST-L-N-SGXX-XX-KT</b> Description: USB type A female shielded SMT plus through hole mounting		
				Checked	Lizzy	07/31/15			
				Drawn	Tina	07/31/15			
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'			
						UNIT: mm			