



P.C.B. LAYOUT

**SPECIFICATIONS**

Current Rating: 1 Amp Max  
 Withstanding: 500V AC for one minute  
 Contact Resistance: 30m Ohms Max  
 Insulation Resistance: 1000M Ohms Min at DC 500V  
 Housing: Thermoplastic, UL94V-0  
 Shell: Steel, Nickel Plating  
 Terminal: Copper Alloy, Gold Plating on Contact  
 Tin on Solder Tail  
 Operating Temp: -25C ~ +85C

Series	Type	Style	Version	Shell Plating	Contact Plating	Color	Package
CUSB	A	CS22	2F8RT	X	SGXX	XX	XX
USB Connector	Type A	See Drawing	Dual Port Female 4 Contacts Each Port, Side Entry Through Hole	N=Nickel (std)	SGXX=Selective Gold XX=Flash if blank, 30=30u"	BK=Black WT=White	TY=Tray Packing

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/15/10
				Checked	Lizzy	05/15/10
				Drawn	Tina	05/15/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-A-CS22-2F8RT-N-SGXX-XX-TY**

Description: USB type A female shielded through hole plus SMT mounting