


**SPECIFICATIONS**

Contact Resistance: 30m Ohm Max.  
 Insulation Resistance: 1000M Ohm Min. At 500VDC  
 Voltage And Current: 1.5A at 250VAC Minimum  
 Withstanding: 750V AC (rms) for 1 Minute  
 Durability: 1500 Cycles  
 Insertion Force: 35 Newton Max.  
 Extraction Force: 10 Newton Minimum

**RoHS compliant**

Item	Name	Material	Finish
1	Housing	Nylon PA9T G.F.	White
2	Terminal	Phos. Bronze T:0.25	Gold/Tin Plated
3	Shell	Brass T:0.3	Nickel Plated

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	06/14/07
				Checked	Lizzy	06/14/07
				Drawn	Tina	06/14/07
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				 UNIT: mm		


**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-A-KS001HL-A1NW-TY**

Description: Modular Jack Side Entry W/O LEDs