



**SPECIFICATIONS**  
 Contact Resistance: 30m Ohm Max.  
 Insulation Resistance: 1000M Ohm Min. At 500VDC  
 Voltage Rating: 250VAC  
 Current Rating: 1.5A  
 Durability: 1500 Cycles  
 Insertion Force: 35 Newton Max.  
 Extraction Force: 10 Newton Min.  
 Withstanding: 750V AC (rms) for 1 Minute

Item	Name	Material	Finish	Remarks
1	Housing	PBT GF	Black	
2	Pin Term.	Phos Bronze: 0.25	Gold-Tin Plated	Gold: 1~3u"; Ni: 40~60u"; Nin:120u"
3	Shell	Brass, T: 0.3	Tin Plated	Tin: 120~200u"
4	Spring Clip	Brass, T:0.3	Tin Plated	Tin: 120~200u"
5	Rear Shell	SPCC, T:0.3	Nickel Plated	
6	Bottom Cover	PBT G.F.	Black	

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-A-KS003-AB-KL**

Description: Triple USB A Type Flat 12 Pin DIP