



**SPECIFICATIONS**  
 Insulation Resistance: 500MM+000D9 Min.  
 Contact Resistance: 50mM+000D9 Max.  
 Withstanding: 1000 VAC 1 minute  
 Current Rating: 1.5A  
 Housing: Thermoplastic UL94V-0  
 Contact: 0.35mm Selective Gold Plating  
 Terminal: 0.35mm Phosphor Bronze  
 Gold and Tin Plating in Solder Area  
 Shield: See Table

Series	Positions	Contacts	LEDs
CUSB-A2/CTJ	8	08	LXX
Mod Jack over USB Type A (x2)	8 Positions	8 Contacts	Left then Right N=None G=Green Y=Yellow O=Orange P=Orange/Green W=Yellow/Green
Color	Plating	Panel Ground	Shield
BK	P1	PGX	S
BK=Black	P1=Gold	Blank=None X:2=Top 4=Top & Sides 6=Top & Sides	S=Shielded

**SUGGESTED PCB LAYOUT  
TOP VIEW**

**RoHS compliant**

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/27/08
				Checked	Lizzy	03/27/08
				Drawn	Tina	03/27/08
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-A2-CTJ-8-08-LXX-BK-P1-PGX-X**

Description: Standard Mod Jack over USB Type A (x2), Panel Mount, Shielded