



SPECIFICATIONS
 Contact Material: Copper Alloy
 Contact Resistance: 50 milliohms max.
 Contact Finish: Gold Plating
 Housing Material: UL 94V-0
 Insulation Resistance: 100 megohms min.
 Shell Material: Copper Alloy
 Shell Plating: Nickel
 Withstanding: 100V AC

RECOMMENDED PCB LAYOUT

Series	Style	Positions	Plating
CUSB-B	JRS11	XX	XX
Mini USB connector type AB	Side entry SMT	04, 05, 08	GDXX=Gold SGXX=Selective Gold XX=Flash if blank, 3, 5, 10, 15, 20, 30u"

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-AB-JRS11-05-XX**

Description: Mini USB Connector, 5 position, side entry surface mount with centering pegs