


SECTION A-A
SCALE 1:1

RoHS compliant

SPECIFICATIONS

- Current Rating: 1.5 Amps
- Withstanding: AC 500V
- Insulation Resistance: 1000Megohms Min.
- Contact Resistance: 30 Milliohms Max.
- Operating Temp: -55C to +85C
- Mating Force: 3.5Kg Maximum
- Unmating Force: 1Kg Minimum
- Contacts: Copper Alloy
- Shell: Copper Alloy

Recommend PCB LAYOUT



Series	Type	Style	Contacts	Material	Shell Plating	Contact Plating	Insulator Color
CUSB	B	204X	4	X	X	SGXX	XX
USB Connector	B Type	Vertical DIP X: M=Male F=Female	4=4 contacts	Blank=PBT A=LCP B=PA6T C=PA9T	N=Nickel (std) T=Tin G=Gold	SGXX=Selective Gold XX: Blank = Flash (V1.1) 30=30u" (V2.0)	WT=White BK=Black BG=Beige

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/09/06
				Checked	Lizzy	08/09/06
				Drawn	Tina	08/09/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

Central Components Manufacturing
440 Lincoln Blvd., Middlesex, New Jersey 08846
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-B-204F-4-N-SG-XX**

Description: USB-B Female 180 DIP