


SECTION A-A
SCALE 1:1

Recommend PCB LAYOUT



SPECIFICATIONS

Current Rating:	1.5 Amps
Withstanding:	AC 500V @ Sea Level
Insulation Resistance:	30 Megohms Min.
Contact Resistance:	30 Milliohms Max.
Mating Force:	3.5Kg Max.
Unmating Force:	1Kg Minimum
Contact Material:	Copper Alloy
Shell:	Copper Alloy
Operating Temp:	-55C to +85C

Series	Type	Style	Contacts	Material	Shell Plating	Contact Plating	Insulator Color
CUSB	B	204X	X	X	X	SGXX	XX
USB Connector	B Type	X: M=Male F=Female	X: 4=4 Contact	Blank=PBT	N=Nickel (std) T=Tin G=Gold	SGXX=Selective Gold XX: Blank = Flash (V1.1) 30=30u" (V2.0)	WT=White (std) BK=Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/09/06
				Checked	Lizzy	08/09/06
				Drawn	Tina	08/09/06
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-B-204F-4-X-N-SGXX-XX**

Description: USB B Female vertical DIP No Cover