



SPECIFICATIONS

Current Rating: 1 Amp Max.
 Withstanding: 100V AC for one minute
 Contact Resistance: 50m Ohms Max.
 Insulation Resistance: 100M Ohms Min ad DC 100V
 Housing: Hi-Temp Thermoplastic, UL94V-0
 Shell: Copper Alloy or SPCC, Nickel Plated
 Terminal: Copper Alloy, Gold Plated on Contact Area
 Tin Plated on Solder Area
 Nickel Underplated Overall
 Operating Temp: -25°C ~ +85°C

Series	Type	Style	Ports/Gender/Cont/ Mount	Material	Shell Plating	Contact Plating	Color
CUSB	B	CS22	1F4VT	A	X	SGXX	WT
USB Connector	Type B	See Drawing	Single Port Female 4 Contacts, Vertical Through Hole mount	A=LCP	N=Nickel (std)	SGXX=Selective Gold XX=Flash (v1.1) if blank, 5, 10, 15, 30u" (v2.0)	WT=White

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	12/08/14
				Checked	Lizzy	12/08/14
				Drawn	Tina	12/08/14
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-B-CS22-1F4VT-A-N-SGXX-WT**

Description: USB type B vertical female shielded through hole mounting