



RECOMMENDED P.C.B. PATTERN LAYOUT

SPECIFICATIONS

- Voltage rating: 30 volts
- Current rating: 1 amp
- Contact material: Bronze
- Contact plating: Gold flash and tin over nickel
- Contact resistance: 50 milliohms max.
- Insulator material: PBT+30% glass fiber or Nylon 6T, UL94V-0, white
- Insulation resistance: 1,000 megohms min.
- Withstanding: 100VAC
- Temperature range: -55°C to +85°C
- Mating force: 35N max.
- Withdrawal force: 10N min.
- Durability: 1,500 cycles min.

Note: White insulator also available.

Series	Type	Style	Options
CUSB	B	JRS2	04FS1BN1A
USB connector	B type	Female right angle	4 position, fully shielded, white insulator, kinked board retention

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-B-JRS2-04FS1BN1A**

Description: USB connector, B type, right-angle, DIP female