



P.C.B. LAYOUT
TOP VIEW ±0.05

SPECIFICATIONS

Housing: Hi-Temp Plastic UL94V-0
 Shell: Copper Alloy, Nickel Plating
 Terminal: Copper Alloy, Gold Plated on contact Area, Tin Plated on Solder Area

Current Rating: 1 Amp Max
 Withstanding: 100V AC for 1 minute
 Contact Resistance: 50m OHMS Max
 Insulation Resistance: 100M OHMS min at DC 100V
 Operation Temp: -0C ~ +50C

Series	Type	POS	Plating	Color	Options
CUSB	MAB	05	SGXX	XX	TR
USB	Mini AB Type	5 Positions	SG=Selective Gold XX: Flash if Blank, 5,10,15,30u"	BK=Black WT=White BG=Beige	TR=Tape & Reel

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
A	dwg	11/30/11	Greg	Approved	Howard	03/20/09
				Checked	Lizzy	03/20/09
				Drawn	Tina	03/20/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-MAB-05-SGXX-XX-TR**
 Description: Mini USB AB Type, PCB Mount, SMT, Metal Shield Female