


SPECIFICATIONS

Housing: Hi-Temp Plastic UL94V-0
 Shell: Copper Alloy, Nickel Plating
 Terminal: Copper Alloy, Gold Plated on contact Area, Tin Plated on Solder Area

Current Rating: 1 Amp Max
 Withstanding: 100V AC for 1 minute
 Contact Resistance: 50m OHMS Max
 Insulation Resistance: 100M OHMS min at DC 100V
 Operation Temp: -0C ~ +50C



P.C.B. LAYOUT
TOP VIEW ±0.05

Series	Type	Style	Ports/Gender/Cont/ Mount	Shell Plating	Contact Plating	Color	Options
CUSB	MB	CS22	1F5RS	N	SGXX	XX	XX
USB Connector	MB=Mini B	See dwg.	Single Port Female, 5 Contacts, Surface mount	N=Nickel	SGXX=Selective Gold XX=Flash if blank, 5, 10, 15, 30u"	WT=White BK=Black BG=Beige	Blank=None CP=Centering Pegs TRF=Tape & Reel with film

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	03/20/09
				Checked	Lizzy	03/20/09
				Drawn	Tina	03/20/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
					UNIT: mm	

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-MB-CS22-1F5RS-N-SGXX-XX-CP-XX**

Description: Mini USB AB Type, PCB Mount, SMT, Metal Shield Female