



SPECIFICATIONS

- Current Rating: 1 Amp Max
- Withstanding: 100V AC or 1 minute
- Contact Resistance: 50m ohms max
- Insulation Resistance: 100M Ohms min at DC 100V
- Housing: Hi-Temp Plastic UL94V-0
- Shell: Copper Alloy, Nickel Plating
- Terminal: Copper Alloy, Gold Plated on Contact
Tin Plating on Solder
- Operating Temp: 0C - +50C

RoHS compliant

Series	Type	Style	Version	Shell Plating	Contact Plating	Color	Package
CUSB	MB	CSMBH	1F5RS	N	SGXX	XX	XX
USB Connector	MB=Mini B	See Drawing	Single Port Female 5 Contacts, Side Entry SMT	N=Nickel (std)	SGXX=Selective Gold XX=Flash (if blank), 30u	BK=Black WT=White BG=Beige	TR=Tape & Reel TB=Tube

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/09/12
				Checked	Lizzy	07/09/12
				Drawn	Tina	07/09/12
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-MB-CSMBH-1F5RS-N-SGXX-XX-XX**

Description: Mini USB type B female shielded SMT mounting