



**SPECIFICATIONS**

- Housing: High Temp Thermoplastic UL94V-0
- LCP E1301
- Contact: Copper Alloy t=0.20mm C5191-EH
- Shell: Copper Alloy t=0.25mm C2680-1/2H
- Current Rating: 1 A Max
- Withstanding: 100V AC for 1 minute
- Contact Resistance: 50mΩ Max.
- Insulation Resistance: 100 MΩ Min
- Total Mating Force: 3.57 Kgf Max.
- Total Unmating Force: 1.0 Kgf Min. 0.81~2.05 Kgf Min. after 10000 insertion/extraction
- Temperature Range: -30°C ~ 80°C

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/10/02
				Checked	Lizzy	07/10/02
				Drawn	Tina	07/10/02
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-UB-JRSA-05FSJT3DBB**

Description: Micro USB type B 5P female SMT style.