



**SPECIFICATIONS**

Voltage Rating: 1A at 30VAC min.  
 Contact Resistance: 50m Ohm Max.  
 Insulation Resistance: 100M Ohm Min. at 500VDC  
 Durability: 1500 Cycles  
 Insertion Force: 35 Newtons Max.  
 Extraction Force: 7 Newtons Min  
 Withstanding: 100V AC

Item	Name	Material	Finish
1	Housing	Nylon PA9T G.F.	Black
2	Pin Terminal	PBS T:0.2	Gold/Tin Plated
3	Shell	Brass T:0.4	Nickel Plated
4	Center Pastern	Nylon PA9T G.F.	Black

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/16/10
				Checked	Lizzy	07/16/10
				Drawn	Tina	07/16/10
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-MB5-KY-KSBD-5-L**

Description: Mini USB B Type 5 Pin Connector DIP