



SPECIFICATIONS
 Current Rating: 0.8A max
 Housing: LCP (UL 94V-0)
 Contacts: Copper Alloy
 Shell: Stainless Steel
 Contact Res: 50 mohm max
 Insulation Res: 100 Mohm min
 Withstanding: 100 VAC

RoHS compliant

Series	Type	Style	Version	Contact Plating	Color	Package
CUSB	UAB	SA13	F5RS	SGXX	X	X
USB Connector	UAB=Micro AB	See Drawing	Single Port Female 5 Contacts, Side Entry SMT	SGXX=Selective Gold XX=Flash if blank, 3, 5, 10, 15, 30u"	K=Black W=White B=Beige	R=Reel Y=Tray B=Tube

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/09/12
				Checked	Lizzy	07/09/12
				Drawn	Tina	07/09/12
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
						UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-UAB-SA13F5RS-SG-K-R**

Description: Micro USB type AB female surface mount, shielded with out post