



SPECIFICATIONS

Current Rating: 1.8 Amp Max. (only pin 1, 5)
 1 AMP Max. for other

Housing: Thermoplastic UL94V-0

Shell: Copper Alloy, Nickel Plating

Terminal: Copper Alloy, Gold Plated on contact area
 Tin plating on solder tail

Withstanding: 100V AC for 1 minute

Contact Resistance: 30m ohms max

Insulation Resistance: 100M ohms min at DC 500V

Operating Temp: -25C ~ +85C

Pin Number	Signal Name
1	VBUS
2	D-
3	D+
4	ID
5	GND
SHELL	SHIELD

Series	Type	Positions	Plating	Package
CUSB-UB	22PJ	05	SGX	TR
Micro USB Type B	Male Wiremount Shielded	05=5 Positions	SG=Selective Gold X=Flash if blank 5,10,15,30 u"	TR=Tray

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/29/09
				Checked	Lizzy	05/29/09
				Drawn	Tina	05/29/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-UB-22PJ-05-SGX-TR**

Description: Micro USB B Type, PCB Mount, Metal Shield, Male, Plug Solder Wire Style