



Pin Number	Signal Name
1	VBUS
2	D-
3	D+
4	ID
5	GND

SPECIFICATIONS

Current Rating: 1 Amp Max.
 Housing: Thermoplastic UL94V-0
 Shell: Copper Alloy, Nickel Plating / Steel
 Terminal: Copper Alloy, Gold Plated on contact area Tin plating on solder tail

Withstanding: 500V AC for 1 minute
 Contact Resistance: 30m ohms max
 Insulation Resistance: 1000M ohms min at DC 500V
 Operating Temp: -25C ~ +85C

Series	Type	Positions	Plating	Package
CUSB-UB	22PNH	05	SGX	TR
Micro USB Type B	Female Wiremount Shielded	05=5 Positions	SG=Selective Gold X=Flash if blank 5,10,15,30 u"	TR=Tray

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/29/09
				Checked	Lizzy	05/29/09
				Drawn	Tina	05/29/09
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
						UNIT: mm

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-UB-22PNH-05-SGX-TR**

Description: Micro USB B Type, Metal Shield, Female Solder Wire Style