



P.C.B. LAYOUT
TOP VIEW ±0.05

SPECIFICATIONS

- Current Rating: 1.8 Amp Max (only Pin 1,5)
Other 1 Amp Max
- Withstanding: 100V AC for 1 minute
- Contact Resistance: 50m ohms max
- Insulation Resistance: 100M Ohms min ad DC 500V
- Housing: Hi-Temp, Plastic UL94V-0
- Shell: Copper Alloy & Stainless Steel
Tin Plating & Nickel Plating
- Terminal: Copper Alloy, Gold Plated Over All
- Operation Temp: -25C ~ +105C

Series	Type	Style	Ports/Gender/Cont/ Mount	Shell Plating	Contact Plating	Package
CUSB	UB	CS22AH	1F5RST	X	GDXX	XX
USB Connector	UB=Micro B	See Drawing	1F5rS=Single Port Female 5 Contacts, Side Entry Through Hole plus SMT	N=Nickel T=Tin (std)	GDXX=Gold XX=Flash if blank, 5,10,15,30u" gold	TR=Tape & Reel

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/08/13
				Checked	Lizzy	05/08/13
				Drawn	Tina	05/08/13
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CUSB-UB-CS22AH-1F5RST-X-GDXX-TR**

Description: Micro USB B Type, SMT Female