



SPECIFICATIONS

- Current Rating: 6A AC/DC
- Voltage Rating: 125 V AC/DC
- Contact Resistance: 10mΩ ohm Max.
- Insulation Resistance: 1000MΩ ohm Min.
- Withstanding: 500V AC/minute
- Ingress Protection: IP67
- Housing Material: PBT, UL94V-0, Black
- Contact Material: Brass
- O-Ring: EPDM
- Nut: Brass
- Contact Plating: Gold Plating 10u" over Nickel (std)
- Nut Plating: 60u" ~ 100u" Nickel Plating
- Temperature Range: -40C ~ +85C

Series	Type	Version	Positions	Plating
CWP	M12	Q11JNM	XX	GD10
Waterproof Circular Connector	M12 Connector	Q11JNM=Male Wire Mount Molded	02 to 05	GD10=10u" gold

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	11/22/12
				Checked	Lizzy	11/22/12
				Drawn	Tina	11/22/12
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3°
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **CWP-M12-Q11JNM-04-XX**

Description: M12 Male for cable